



PW-C40

SPECIAL MODEL

PRESSURE

FLOW RATE

ABSORBED POWER

 $100 \, \text{bar}$

 $300\,l/h$

1,3 kW





HIGHPURE - HPE CODE: APTA40015

TECNOLOGIE ESCLUSIVE

- DELAYED TOTAL STOP DTS
- MICRO LEAKAGE CONTROL
- MLC
- LANCE NOZZLE CLOGGED CONTROL NCC
- WORKING HAURS COUNTERWHC
- FLOODING PREVENTION SYSTEM FPS

TO BE USED ONLY IN COMBINATION WITH APTA40015 HIGHPURE HPE (SEE IMAGE ON THE RIGHT)

MOST FREQUENTLY USE

CONSTRUCTION INDUSTRY

GREEN ENERGIES

NAUTICAL/AUTO/TRANSPORTS

GREENHOUSES/GLASSHOUSES/ TENSILE STRUCTURES

INNOVATIONS







SPECS



IPC PUMP WITH SEPARATE BY-PASS, PROVIDED WITH PRESSURE ADJUSTMENT KNOB



PROFESSIONAL HOSE REEL



INTEGRATED ERGONOMIC HANDLE, LANCE HOLDER

TECHNICAL DATA

PW-C40 D1005P4 M

Code		IDAF40884
PERFORMANCE		
Operating pressure max	bar/Mpa	100/10
Flow rate	l/h	300
Inlet water max. temperature	°C	50
Power supply	Ph-V-Hz/A	1-230-50/8,6
Absorbed power	kW	1,3
Motor pole/rpm		4-1400
Remote control		DTS
Pump/head/pistons		Ipc plunger/brass/ceramic
Detergent tank	l	7,5
Detergent delivery		low pressure
Dimension (LxWxH)	cm	74x43x81
Weight	Ka	47

STANDARD EQUIPMENT

CODE: IPPR40025
HANDGRIP G6000

CODE: LCPR40013
EXTENSION P70 HY.JET

CODE: UGLN40038 H.P. NOZZLE 1/4 1502 CODE: TBAP40012 H.P. HOSE 1/4" 10 m









OPTIONAL ACCESSORIES

CODE: LCPR29360
MUDGUARD LANCE P90

CODE: RCIN10810
HOSE COUPLINGS

CODE: TBAP23853

DRAIN KIT 10 m

CODE: SPID24939 FIXED HYDROBRUSH LANCE



CODE: KTRI40478 KIT FOR HOT WATER FEEDING VERSION





