



IPC

BY TENNANT COMPANY

AUTOMATIC SCRUBBERS - WALK-BEHIND

CT105

The CT105 is recommended for medium to large spaces and has been designed to be very easy to use, while keeping electronics to a minimum. The CT105 features a constant flow technology for full control of water flow, a large brush head and an "oversized" opening to the recovery tank for easy clean out. The CT105 is the most reliable, productive and simple machine in its category.

MOST FREQUENT USE

RETAIL



HOSPITALITY



CLEANING CONTRACTORS



EDUCATION



MAX PRODUCTIVITY

27,000-
31,000 ft²/h

BATTERY RUNNING TIME

3.7 - 5.0 h

KEY SPECS

20/34 gal


28", 32" traction drive



NEW LARGE COVER



NEW ERGONOMIC HANDLE



HIGH QUALITY MOTOR GEAR



INNOVATIONS



SLSTSM
SELF
LEVELING
SYSTEM



YELLOW
TOUCH
POINTS

| | | CT105 BT70 TRACTION | CT105 BT85 TRACTION |
|---|--|---|--|
| Max theoretical productivity | ft ² /h - m ² /h | 27,000 ft ² / 3,150 m ² | 31,000 ft ² / 3,825m ² |
| Cleaning path | in / mm | 28" / 700 mm | 32" / 850 mm |
| Water tank capacity (solution recovery) | gal/ l | 26/ 27 gal - 100/110 l | 26/ 27gal - 100/110 l |
| Max running time | min | 360 | 360 |
| Voltage | V | 24 (4 X 6) | 24 (4 X 6) |
| Installed power | W | 650 | 650 |
| Squeegee width | in/ mm | 37 in/ 942 mm | 37 in/ 942 mm |
| Max speed | mph/ kph | 2.8 mph/ 4.5 kph | 2.8 mph/ 4.5 kph |
| Weight (w/o batteries) | lbs/ kg | 375 lbs/ 170 kg | 381 lbs/ 232 kg |
| Noise level | DB | 71 dB | 71 dB |