



IPC

BY TENNANT COMPANY

AUTOMATIC SCRUBBERS - RIDERS

CT160

The CT160 rider scrubber is designed for commercial and warehouse cleaning applications and is one of the easiest riders to use on the market. Even the brushes are designed to connect and disconnect automatically. It is available in an optional cylindrical version, which works to pre-sweep while scrubbing, greatly reducing the time required for a job.

MOST FREQUENT USE

RETAIL



HOSPITALITY



CLEANING CONTRACTORS



EDUCATION



INTUITIVE CONTROL PANEL



PRE-SWEEP SYSTEM ON CYLINDRICAL MODEL



SEPARATE DETERGENT DOSING SYSTEM

MAX PRODUCTIVITY

39,000-
50,000 ft²/h

**BATTERY
RUNNING TIME**

4.7 - 5.0 h

KEY SPECS

38/45 gal

28", 32", 36"
30" cylindrical rider



INNOVATIONS



SL5™
SELF
LEVELING
SYSTEM



YELLOW
TOUCH
POINTS

		CT160 BT70 RIDER	CT160 BT85 RIDER	CT160 BT95 RIDER	CT160 BT75R RIDER
Max theoretical productivity	ft ² /h - m ² /h	38,980 ft ² / 4,550 m ²	44,550 t ² / 5,525 m ²	50,119 ft ² / 6,175 m ²	41,766 ft ² / 4,875 m ²
Cleaning path	in / mm	28" / 700 mm	32" / 850 mm	37" / 950 mm	30" / 750 mm
Water tank capacity (solution recovery)	gal / l	39/45 gal - 145/17 l	39/45 gal - 145/17 l	39/45 gal - 145/17 l	39/45 gal - 145/17 l
Max running time	min	300	300	300	300
Voltage	V	36V	36V	36V	36V
Installed power	W	650	650	650	670
Squeegee width	in / mm	33" / 830 mm	40" / 1010 mm	44" / 1100 mm	40" / 1010 mm
Max speed	mph / kph	4.0 mph / 6.5 kph	4.0 mph / 6.5 kph	4.0 mph / 6.5 kph	4.0 mph / 6.5 kph
Weight (w/o batteries)	lbs / kg	602 Lbs / 273 Kg	639 Lbs / 290 Kg	644 Lbs / 292 Kg	617 lbs / 280 kg
Dimensions (l x w x h)	in / mm	68 x 34 x 54 in	68 x 34 x 54 in	68 x 34 x 54 in	72 x 42 x 54 in
Noise level	dB	72 dB	72 dB	72 dB	72 dB