



IPC

BY TENNANT COMPANY

ULTRAPUREWINDOWCLEANING

HYDROCART™ JR.

The HydroCart Jr., with its 41.5" low profile, is designed for easy transportation while maximizing results. This system produces pure water to meet the needs of both commercial and residential window cleaners. The HydroCart Jr. comes in 3 configurations to accommodate the needs of Professional Window Cleaners and Building Service Contractors.

MOST FREQUENT USE

RETAIL



HOSPITALITY



CLEANING CONTRACTORS



EDUCATION



CLEANS UP TO 3 STORIES



SCREEN WASHER TOOL (OPTIONAL)

MAX PRODUCTION

.25 - 1.5 gpm

NUMBER OF USERS

1-2

CLEANING HEIGHT

1-5 stories (DI Only)

1-2 stories (RO Only)

1-2 stories (RO & DI)



3-STAGE SYSTEM
RO, DI, Pre-Filter



SINGLE STAGE SYSTEM
DI Only

PRODUCTIVITY

		HYDROCART JR. DI ONLY	HYDROCART JR. RO ONLY	HYDROCART JR. DI & RO
Part Number		JR-DI	JR-RO	HYDROCART-JR
Power		Supply Water	Supply Water	Supply Water
Dimensions	INCHES	23" X 15.5" X 41.5"	23" X 15.5" X 41.5"	23" X 15.5" X 41.5"
Packaged Dimensions	INCHES	39" X 16" X 25"	39" X 16" X 25"	39" X 16" X 25"
Packaged Weight	LBS.	71 lbs.	71 lbs.	71 lbs.
Pure Water Flow	GPM	1.5 gpm	.6 +/- .25 gpm	.6 +/- .25 gpm
Cleaning Height	FLOOR	1-5 floors	1-2 floors	1-2 floors
Working Hose Length	FEET/CM	50'/1524 cm	50'/1524 cm	50'/1524 cm
Filtration	STAGES	1	2	3
DI and Carbon Filters	INCHES	4.5" X 10"	4.5" X 10" & 2.5" X 10"	4.5" X 10" & 2.5" X 10"